E-link Digitizer

NULL-3

Quality by Design

High accuracy industrial digitizer



E-link is a high performance digitizer tablet well suited for CAD, mapping and GIS applications as well as drawing, tracing and presentation graphics. These top of the line tablets offer the highest resolution and accuracy available on the market today along with easy-to-use software and programmable function keys. E-link combines all the advantages of a cursor and a digitizer to eliminate multiple input devices and provide you with a sleek, simplified desktop. You can choose from a wide range of options to help you create a working environment suited to your application.

Compatible with other digitizers Almost works with all CAD systems Can store 3 different types of settings Maximum 32 configurable function keys Flexible setting of parameters Parameters can be set from both computer and digitizer itself Firmware is upgradeable from internet 48 kinds of default CAD systems setting.





E-link Digitizer Specification & Estimated Operating Costs

	E-link Digitizer	
Model	A0 (36"×48")	A00 (44"×60")
Input Voltage	220V @ 50HZ	
Working Voltage	13V AC	
Power consumption	11W	
Current Draw	800 mA	
Resolution	100 ~1000LPI, 8 ~100LPM	
Accuracy	0.254mm	
Proximity	Up to 5 cm	
Output speed	1 ~ 100 pair/s	
Operating Temperature	10°C - 40°C	
Humidity Range	0% to 95%, non-condensing	
Temperature Modulus	5 PPM	
Certification	CE certified	
Interface:	RS232	
Keyboard	Wearable keys, 16keys . 32 keys.	
Stop Bits	1, 2	
Data Bits	7,8	
Parity	EVEN, ODD, NONE	
Baud Rate	1200, 2400, 4800, 9600, 19200	
Data format	Support 20 kinds of ASCII format and	
	11 kinds of Binary format	
Stand	Height and Angle adjustable, easy install	
Packing Size:	127 × 16 × 160 cm (Tablet)	$147 \times 16 \times 88$ (Tablet)
	$73 \times 24 \times 87$ cm (Stand)	$73 \times 24 \times 87$ cm (Stand)
Net Weight	30Kg (Tablet)	45 Kg
	10Kg (Stand)	10Kg (Stand)
Gross Weight	48Kg (Tablet and Stand)	53 Kg

Authorized Local dealer:

